


## MIRAGE 600

Electropneumatic sawing machine with up-feed blade and automatic feeding device




A (mm)	B (mm)	C (mm)	Kg
2400	1550	1960	850

### Technical characteristics:



- 400, 500 or 600 mm blade with fixed cut at 90°
- Vice cylinders on the worktable: 2 horizontals and 2 verticals with system of locking (+vice cylinder loader and infeed profile on the left side for alignment of the bar)
- Automatic or manual cutting (with stop positioned on feed carriage)
- Hydraulic bar feed with Ø50 cylinder
- Piece feed by recirculating ball screws, linear guides, double or triple pitch (0 - 475 mm) and brushless drive
- Blade exit control linear transducer
- Door for replacement blade, RH side with security equipment
- Motorization with belt transmission
- Work table width 65 on Left and 150 on Right
- Max. bar waste 105 mm
- Option of fitting electric or pneumatic drilling units (max 2) for holes diam. 6-7 mm or punch press units
- Micro-drop pure oil blade lubrication system
- Motor M112 7,5 kW (starting with Soft-Start)
- Soundproofing integral guard with soundproofing tunnel
- Cutting lists entered via floppy disk/keyboard
- Electronic equipment Microvision

## CUTTING DIAGRAM

N.B. La macchina di serie può equipaggiare le lame Ø600, Ø500 e Ø400  
Con lama Ø355 non è possibile cambiare il diametro lama



**DIMENSIONS AND WEIGHT**




**STANDARD ACCESSORIES:**

n°	Description
1	∅ 600 mm tungsten carbide saw blade
3	Horizontal vices
2	Vertical vices
	Integral guard kit
1	Transducer for control of blade exit position
1	Micro-drop blade lubrication system using pure oil
	Possibility of change blade
	Set up for forced evacuation of chips and fumes collectors

**OPTIONALS:**


n°	Description	Code
	Special vices	On estimate
1	400 loading roller table 2,8 mt.	PR-26281
1	400 loading roller table 4,7mt.	PR-25854
	Additional charge for special voltage and cycle (Standard motor 230/400V three-phase 50HZ)	ZG-79126
	Additional charge for plant version UL-CSA (The additional charge includes the plant with cables and special components)	ZG-79158
	∅500 blade for aluminium profiles, blade thickness 4mm	GP306110
	Thin ∅400 blade for aluminium profiles, blade thickness 3,2mm	GP306109
	∅400 blade for aluminium profiles, blade thickness 4mm	GP306108
	Kit accessories for connection swarf exhauster Mirage 600	PR-27335
	Kit accessories for connection swarf exhauster Mirage 600	PR-27341
	Crate packing	FC305715

Carton pallet packing with heat-shrink plastic bag:



A (mm)	B (mm)	C (mm)	Kg
260	175	180	900

Crate packing overall dimensions:



A (mm)	B (mm)	C (mm)	Kg
260	175	180	950